



10'X10' WORK SHELTER

BUILT TOUGH - VERSATILE SHELTER FOR ANY JOB

The DEWALT® Work Shelter delivers fast setup, rugged protection, and proven durability for demanding jobsites. Its reinforced steel frame with a cross-brace ceiling structure provides reliable support when it counts. The Duralon® PLUS fabric top offers UPF 50+ UV protection to keep your crew covered, while the Wide-Trax™ roller bag with high-density wheels ensures smooth transport and easy storage.

FEATURES

- **High Strength Steel Frame**
Powder-coated 1015 steel provides reliable durability in outdoor environments.
- **Cross-Brace Ceiling Structure**
Bolt-on canopy top anchors to reinforced cross-bracing for consistent performance and support during frequent use.
- **Duralon® PLUS Fabric Top**
Multi-layer polyester top offers water repellency, UPF 50+ UV protection with reinforced elongated fabric corners.
- **E-Z Glide™ Leg Adjusters**
Built-in channels allow for smooth height adjustments, even on uneven or debris-covered surfaces.
- **E-Z Adjust Corners**
Quick-deploy design enables safe, hassle-free setup and takedown with minimal effort.
- **Reinforced Foot**
Durable Nylon Foot Plate with a Wide Base for Maximum Stability.
- **Wide-Trax™ Roller Bag Included**
Heavy-duty rolling storage bag makes transport and storage easy between locations.
- **Signature DEWALT® branding and color treatment on shelter and roller bag**



TECHNOLOGY



SPECIFICATIONS

SHADED AREA	100 sq ft (9 sq. m)	MAXIMUM VALANCE CLEARANCE HEIGHT	6' 8" (2.0 m)
ITEM WEIGHT	53 lbs. (24 kg)	TOP FABRIC	Duralon® PLUS - 300D Polyester
SHIPPING DIMENSIONS	65" L x 11" W x 8.5" H (165 cm x 28 cm x 22 cm)	FIRE CERTIFICATION	Meets the CPAI-84, NFPA-701, & CAN/ULC-S109 Fire-Resistance Requirements
SHIPPING WEIGHT	63.2 lbs. (28.7 kg)	WARRANTY	3 Year
MAXIMUM PEAK HEIGHT	11' 3.5" (3.4 m)		
MAXIMUM HEADROOM	6' 9.5" (2.1 m)		

DEWALT®

10'X10' WORK SHELTER

International E-Z UP, Inc.
1900 Second Street
Norco, California 92860
(951) 279-0999 • FAX (800) 810-8775

TO ORDER:
(800) 45-SHADE
(800) 457-4233